

CATALOG No: **BC2N002-4C**

ISSUED: 28-Apr-22

GENERAL INFORMATION

HP	KW	Pole	RPM	Frame	Voltage	Hz	Phase	IP Rating
2	1.50	2	3600	145TC	230/460 V	60	3	IP55

Enclosure	Ins. Class	Service Factor	Time Rating	NEMA Design	Rated Amb.	Rated Altitude
TEFC	F	1.25	Continuous	B	-15 to 40 C*	<3300 ft

TYPICAL PERFORMANCE

Efficiency (%)			Power Factor (%)		
Full Load	3/4 Load	1/2 Load	Full Load	3/4 Load	1/2 Load
85.5	85.8	85.5	0.86	0.82	0.74

LRT%	BDT %	Full Load Amps	Locked Rotor Amps	Full Load RPM
		460 V	460 V	
300	330	2.60	19.50	3490

NEMA KVA Code	Bearing Size		Oil Seal		Sound Level
	Drive End	Non-Drive End	Drive End	Non-Drive End	dB(A)
J	62052Z	62032Z	25 x 35 x 7	17 x 28 x 6	72

*Weights shown are estimated and based on standard foot mounted motor designs

VFD DUTY INFORMATION

	Variable Torque	Constant Torque	Rating
-	3 - 60 Hz	4 - 60 Hz	CSA Approved Class I; Div 2; Groups A, B, C, & D, T3
-	-	-	

Click Link Below For Drawing

<http://brookcrompton.com/Drawings/W-NEMA/NEMA%20Cast%20Iron%20B34/WP-DF143.5TC.pdf>

Click Link Below For Connection Diagram

<http://www.brookcrompton.com/Connections/Connection%20Diagram%209%20Lead%202X4%20NEMA.pdf>

Notes:

CATALOG No: **BC2N002-4C**

ISSUED: 28-Apr-22

GENERAL INFORMATION

HP	KW	Pole	RPM	Frame	Voltage	Hz	Phase	IP Rating
2	1.50	2	3000	145TC	400 V	50	3	IP55

Enclosure	Ins. Class	Service Factor	Time Rating	NEMA Design	Rated Amb.	Rated Altitude
TEFC	F	1.00	S1	B	-15 to 40 C°	<3300 ft

TYPICAL PERFORMANCE

Efficiency (%)			Power Factor (%)		
Full Load	3/4 Load	1/2 Load	Full Load	3/4 Load	1/2 Load
84.0	85.5	85.5	0.91	0.89	0.82

LRT %	BDT %	Full Load Amps		Locked Rotor Amps		Full Load RPM
		400 V		400 V		
300	330	2.99		22.43		2840

NEMA KVA Code	Bearing Size		Oil Seal		Sound Level
	Drive End	Non-Drive End	Drive End	Non-Drive End	dB(A)
J	62052Z	62032Z	25 x 35 x 7	17 x 28 x 6	72

*Weights shown are estimated and based on standard foot mounted motor designs

VFD DUTY INFORMATION

	Variable Torque	Constant Torque	Rating
-	3 - 60 Hz	4 - 60 Hz	CSA Approved Class I; Div 2; Groups A, B, C, & D, T3
-	-	-	

Click Link Below For Drawing

<http://brookcromptonna.com/Drawings/W-NEMA/NEMA%20Cast%20Iron%20B34/WP-DF143.5TC.pdf>

Click Link Below For Connection Diagram


<http://www.brookcromptonna.com/Connections/Connection%20Diagram%209%20Lead%202X4%20NEMA.pdf>

Notes:

Motor: BC2N002-4C

	Frame:	145TC	2 HP	460 V	
	Pole no.:	2	3.0 ft.lbs.	60 Hz	3490 rpm

Speed	0	720	1440	2160	2880	3492	3490	3600
Speed ratios	0	0.2	0.4	0.6	0.8	0.97	0.969	1
Mot. torque ratios	3	2.6	1.9	1.8	1.8	3.3	1	0
Motor torque / ft.lbs.	9	8	6	6	5	10	3	0




*Curve base on calculated values

Motor: BC2N002-4C

	Frame:	145TC	2 HP	400 V	
	Pole no.:	2	3.7 ft.lbs.	50 Hz	2840 rpm

Speed	0	600	1200	1800	2400	2910	2840	3000
Speed ratios	0	0.2	0.4	0.6	0.8	0.97	0.947	1
Mot. torque ratios	3	2.6	1.9	1.8	1.8	3.3	1	0
Motor torque / ft.lbs.	11	10	7	7	7	12	4	0



*Curve base on calculated values