

CATALOG No: **BC2N010-4D**

ISSUED: 28-Apr-22

GENERAL INFORMATION

HP	KW	Pole	RPM	Frame	Voltage	Hz	Phase	IP Rating
10	7.50	2	3600	215TD	230/460 V	60	3	IP55

Enclosure	Ins. Class	Service Factor	Time Rating	NEMA Design	Rated Amb.	Rated Altitude
TEFC	F	1.25	Continuous	B	-15 to 40 C*	<3300 ft

TYPICAL PERFORMANCE

Efficiency (%)			Power Factor (%)		
Full Load	3/4 Load	1/2 Load	Full Load	3/4 Load	1/2 Load
90.2	91.0	90.2	0.90	0.89	0.79

LRT%	BDT %	Full Load Amps	Locked Rotor Amps	Full Load RPM
		460 V	460 V	
240	500	11.60	90.00	3515

NEMA KVA Code	Bearing Size		Oil Seal		Sound Level
	Drive End	Non-Drive End	Drive End	Non-Drive End	dB(A)
J	62082Z	63052Z	40 x 52 x 7	25 x 37 x 7	60

*Weights shown are estimated and based on standard foot mounted motor designs

VFD DUTY INFORMATION

	Variable Torque	Constant Torque	Rating
-	3 - 60 Hz	4 - 60 Hz	CSA Approved Class I; Div 2; Groups A, B, C, & D, T3
-	-	-	

Click Link Below For Drawing

<http://brookcrompton.com/Drawings/W-NEMA/NEMA%20Cast%20Iron%20B35/WP-DF213.5TD.pdf>

Click Link Below For Connection Diagram

<http://www.brookcrompton.com/Connections/Connection%20Diagram%209%20Lead%20X4%20NEMA.pdf>

Notes:

CATALOG No: **BC2N010-4D**

ISSUED: 28-Apr-22

GENERAL INFORMATION

HP	KW	Pole	RPM	Frame	Voltage	Hz	Phase	IP Rating
10	7.50	2	3000	215TD	400 V	50	3	IP55

Enclosure	Ins. Class	Service Factor	Time Rating	NEMA Design	Rated Amb.	Rated Altitude
TEFC	F	1.00	S1	B	-15 to 40 C°	<3300 ft

TYPICAL PERFORMANCE

Efficiency (%)			Power Factor (%)		
Full Load	3/4 Load	1/2 Load	Full Load	3/4 Load	1/2 Load
88.5	90.5	91.0	0.91	0.93	0.93

LRT %	BDT %	Full Load Amps		Locked Rotor Amps		Full Load RPM
		400 V		400 V		
240	500	13.34		103.50		2860

NEMA KVA Code	Bearing Size		Oil Seal		Sound Level
	Drive End	Non-Drive End	Drive End	Non-Drive End	dB(A)
J	62082Z	63052Z	40 x 52 x 7	25 x 37 x 7	60

*Weights shown are estimated and based on standard foot mounted motor designs

VFD DUTY INFORMATION

	Variable Torque	Constant Torque	Rating
-	3 - 60 Hz	4 - 60 Hz	CSA Approved Class I; Div 2; Groups A, B, C, & D, T3
-	-	-	

Click Link Below For Drawing

<http://brookcromptonna.com/Drawings/W-NEMA/NEMA%20Cast%20Iron%20B35/WP-DF213.5TD.pdf>


Click Link Below For Connection Diagram

<http://www.brookcromptonna.com/Connections/Connection%20Diagram%209%20Lead%202X4%20NEMA.pdf>

Notes:

Motor: BC2N010-4D				
	Frame:	215TD	10 HP	460 V
	Pole no.:	2	14.9 ft.lbs.	60 Hz
				3515 rpm


Speed	0	720	1440	2160	2880	3492	3515	3600
Speed ratios	0	0.2	0.4	0.6	0.8	0.97	0.976	1
Mot. torque ratios	2.4	2.1	1.5	1.5	1.5	5	1	0
Motor torque / ft.lbs.	36	31	23	22	22	75	15	0



*Curve base on calculated values

Motor: BC2N010-4D				
Frame:	215TD	10 HP	400 V	
Pole no.:	2	18.4 ft.lbs.	50 Hz	2860 rpm

Speed	0	600	1200	1800	2400	2910	2860	3000
Speed ratios	0	0.2	0.4	0.6	0.8	0.97	0.953	1
Mot. torque ratios	2.4	2.1	1.5	1.5	1.5	5	1	0
Motor torque / ft.lbs.	44	38	28	27	27	92	18	0



*Curve base on calculated values