

CATALOG No: **BC4N1.5-4D**

ISSUED: 28-Apr-22

GENERAL INFORMATION

HP	KW	Pole	RPM	Frame	Voltage	Hz	Phase	IP Rating
1.5	1.10	4	1800	145TD	230/460 V	60	3	IP55

Enclosure	Ins. Class	Service Factor	Time Rating	NEMA Design	Rated Amb.	Rated Altitude
TEFC	F	1.25	Continuous	B	-15 to 40 C*	<3300 ft

TYPICAL PERFORMANCE

Efficiency (%)			Power Factor (%)		
Full Load	3/4 Load	1/2 Load	Full Load	3/4 Load	1/2 Load
86.5	86.0	84.5	0.76	0.67	0.56

LRT%	BDT %	Full Load Amps	Locked Rotor Amps	Full Load RPM
		460 V	460 V	
420	400	2.10	16.50	1745

NEMA KVA Code	Bearing Size		Oil Seal		Sound Level
	Drive End	Non-Drive End	Drive End	Non-Drive End	dB(A)
K	62052Z	62032Z	25 x 35 x 7	17 x 28 x 6	57

*Weights shown are estimated and based on standard foot mounted motor designs

VFD DUTY INFORMATION

	Variable Torque	Constant Torque	Rating
-	3 - 60 Hz	4 - 60 Hz	CSA Approved Class I; Div 2; Groups A, B, C, & D, T3
-	-	-	

Click Link Below For Drawing

<http://brookcrompton.com/Drawings/W-NEMA/NEMA%20Cast%20Iron%20B35/WP-DF143.5TD.pdf>

Click Link Below For Connection Diagram

<http://www.brookcrompton.com/Connections/Connection%20Diagram%209%20Lead%20X4%20NEMA.pdf>

Notes:

CATALOG No: **BC4N1.5-4D**

ISSUED: 28-Apr-22

GENERAL INFORMATION

HP	KW	Pole	RPM	Frame	Voltage	Hz	Phase	IP Rating
1.5	1.10	4	1500	145TD	400 V	50	3	IP55

Enclosure	Ins. Class	Service Factor	Time Rating	NEMA Design	Rated Amb.	Rated Altitude
TEFC	F	1.00	S1	B	-15 to 40 C°	<3300 ft

TYPICAL PERFORMANCE

Efficiency (%)			Power Factor (%)		
Full Load	3/4 Load	1/2 Load	Full Load	3/4 Load	1/2 Load
80.0	82.0	81.5	0.82	0.77	0.66

LRT %	BDT %	Full Load Amps		Locked Rotor Amps		Full Load RPM
		400 V		400 V		
420	400	2.42		18.98		1400

NEMA KVA Code	Bearing Size		Oil Seal		Sound Level
	Drive End	Non-Drive End	Drive End	Non-Drive End	dB(A)
K	62052Z	62032Z	25 x 35 x 7	17 x 28 x 6	57

*Weights shown are estimated and based on standard foot mounted motor designs

VFD DUTY INFORMATION

	Variable Torque	Constant Torque	Rating
-	3 - 60 Hz	4 - 60 Hz	CSA Approved Class I; Div 2; Groups A, B, C, & D, T3
-	-	-	

Click Link Below For Drawing

<http://brookcromptonna.com/Drawings/W-NEMA/NEMA%20Cast%20Iron%20B35/WP-DF143.5TD.pdf>

Click Link Below For Connection Diagram


<http://www.brookcromptonna.com/Connections/Connection%20Diagram%209%20Lead%202X4%20NEMA.pdf>

Notes:

Motor: BC4N1.5-4D

	Frame:	145TD	1.5 HP	460 V	
	Pole no.:	4	4.5 ft.lbs.	60 Hz	1745 rpm


Speed	0	360	720	1080	1440	1746	1745	1800
Speed ratios	0	0.2	0.4	0.6	0.8	0.97	0.969	1
Mot. torque ratios	4.2	3.6	2.7	2.6	2.5	4	1	0
Motor torque / ft.lbs.	19	16	12	12	11	18	5	0



*Curve base on calculated values

Motor: BC4N1.5-4D				
	Frame:	145TD	1.5 HP	400 V
	Pole no.:	4	5.6 ft.lbs.	50 Hz
				1400 rpm

Speed	0	300	600	900	1200	1455	1400	1500
Speed ratios	0	0.2	0.4	0.6	0.8	0.97	0.933	1
Mot. torque ratios	4.2	3.6	2.7	2.6	2.5	4	1	0
Motor torque / ft.lbs.	24	20	15	14	14	23	6	0



*Curve base on calculated values