

CATALOG No: **BC6N005-5C**

ISSUED: 28-Apr-22

**GENERAL INFORMATION**

HP	KW	Pole	RPM	Frame	Voltage	Hz	Phase	IP Rating
5	4.00	6	1200	215TC	575 V	60	3	IP55

Enclosure	Ins. Class	Service Factor	Time Rating	NEMA Design	Rated Amb.	Rated Altitude
TEFC	F	1.25	Continuous	B	-15 to 40 C*	<3300 ft

**TYPICAL PERFORMANCE**

Efficiency (%)			Power Factor (%)		
Full Load	3/4 Load	1/2 Load	Full Load	3/4 Load	1/2 Load
89.5	90.1	89.3	0.74	0.75	0.64

LRT%	BDT %	Full Load Amps	Locked Rotor Amps	Full Load RPM
		575 V	575 V	
230	220	5.70	35.90	1165

NEMA KVA Code	Bearing Size		Oil Seal		Sound Level
	Drive End	Non-Drive End	Drive End	Non-Drive End	dB(A)
J	62082Z	63052Z	40 x 52 x 7	25 x 37 x 7	56

\*Weights shown are estimated and based on standard foot mounted motor designs

**VFD DUTY INFORMATION**

	Variable Torque	Constant Torque	Rating
-	3 - 60 Hz	4 - 60 Hz	CSA Approved Class I; Div 2; Groups A, B, C, & D, T3
-	-	-	

**Click Link Below For Drawing**

<http://brookcrompton.com/Drawings/W-NEMA/NEMA%20Cast%20Iron%20B34/WP-DF213.5TC.pdf>

**Click Link Below For Connection Diagram**

<http://www.brookcrompton.com/Connections/Connection%20Diagram%203%20Lead%20575%20NEMA.pdf>

Notes:

CATALOG No: **BC6N005-5C**

ISSUED: 28-Apr-22

**GENERAL INFORMATION**

HP	KW	Pole	RPM	Frame	Voltage	Hz	Phase	IP Rating
5	4.00	6	-	215TC	-	50	3	IP55

Enclosure	Ins. Class	Service Factor	Time Rating	NEMA Design	Rated Amb.	Rated Altitude
TEFC	F	-	S1	B	-15 to 40 C°	<3300 ft

**TYPICAL PERFORMANCE**

Efficiency (%)			Power Factor (%)		
Full Load	3/4 Load	1/2 Load	Full Load	3/4 Load	1/2 Load
86.5	87.5	87.0	0.81	0.78	0.69

LRT %	BDT %	Full Load Amps	Locked Rotor Amps	Full Load RPM
		-	-	
230	220	-	-	-

NEMA KVA Code	Bearing Size		Oil Seal		Sound Level
	Drive End	Non-Drive End	Drive End	Non-Drive End	dB(A)
J	62082Z	63052Z	40 x 52 x 7	25 x 37 x 7	56

\*Weights shown are estimated and based on standard foot mounted motor designs

**VFD DUTY INFORMATION**

	Variable Torque	Constant Torque	Rating
-	3 - 60 Hz	4 - 60 Hz	CSA Approved Class I; Div 2; Groups A, B, C, & D, T3
-	-	-	

**Click Link Below For Drawing**

<http://brookcromptonna.com/Drawings/W-NEMA/NEMA%20Cast%20Iron%20B34/WP-DF213.5TC.pdf>

**Click Link Below For Connection Diagram**


<http://www.brookcromptonna.com/Connections/Connection%20Diagram%203%20Lead%20575%20NEMA.pdf>

Notes:

**Motor: BC6N005-5C**

	<b>Frame:</b>	215TC	5 HP	575 V	
	<b>Pole no.:</b>	6	22.5 ft.lbs.	60 Hz	1165 rpm

<b>Speed</b>	0	240	480	720	960	1164	1165	1200
<b>Speed ratios</b>	0	0.2	0.4	0.6	0.8	0.97	0.971	1
<b>Mot. torque ratios</b>	2.3	2.0	1.5	1.4	1.4	2.2	1	0
<b>Motor torque / ft.lbs.</b>	52	45	33	32	31	50	23	0



\*Curve base on calculated values

50HZ Speed-Torque Curve not available for this motor

				<b>Motor: BC6N005-5C</b>	
	<b>Frame:</b>	215TC	5 HP	400 V	
	<b>Pole no.:</b>	6	- ft.lbs.	50 Hz	- rpm

<b>Speed</b>	0	200	400	600	800	970	-	1000
<b>Speed ratios</b>	0	0.2	0.4	0.6	0.8	0.97	-	1
<b>Mot. torque ratios</b>	2.3	2.0	1.5	1.4	1.4	2.2	1	0
<b>Motor torque / ft.lbs.</b>	-	-	-	-	-	-	-	-



\*Curve base on calculated values