

**BALDOR® • RELIANCE** 

**Product Information Packet**

**VXT3152T-210**

**15HP,3500RPM,3PH,60HZ,215TC,0750M,TEFC,F**

Part Detail							
Revision:	C	Status:	PRD/A	Change #:		Proprietary:	No
Type:	AC	Elec. Spec:	07WGR536	CD Diagram:	CD0005	Mfg Plant:	
Mech. Spec:		Layout:	07LYL289	Poles:	02	Created Date:	12-02-2020
Base:		Eff. Date:	04-07-2021	Leads:	9#14		

Specs			
Catalog Number:	VXT3152T-210	Electrically Isolated Bearing:	Not Electrically Isolated
Enclosure:	TEFC	Feedback Device:	NO FEEDBACK
Frame:	215TC	Heater Indicator:	No Heater
Frame Material:	Iron	Insulation Class:	F
Output @ Frequency:	15.000 HP @ 60 HZ	Inverter Code:	Inverter Duty
Synchronous Speed @ Frequency:	3600 RPM @ 60 HZ	IP Rating:	NONE
Voltage @ Frequency:	460.0 V @ 60 HZ	KVA Code:	H
	230.0 V @ 60 HZ	Lifting Lugs:	Standard Lifting Lugs
	208.0 V @ 60 HZ	Locked Bearing Indicator:	Locked Bearing
XP Class and Group:	CLI GP A,B,C,D	Motor Lead Termination:	Flying Leads
XP Division:	Division II	Motor Type:	0750M
Agency Approvals:	CCSA US	Mounting Arrangement:	F1
	CSA EEV	Power Factor:	91
	NEMA PREMIUM	Product Family:	General Purpose
	UR	Pulley Face Code:	C-Face
Auxillary Box:	No Auxillary Box	Rodent Screen:	None
Auxillary Box Lead Termination:	None	Shaft Ground Indicator:	No Shaft Grounding
Base Indicator:	No Mounting	Shaft Rotation:	Reversible

<b>Bearing Grease Type:</b>	Polyrex EM (-20F +300F)	<b>Speed Code:</b>	Single Speed
<b>Blower:</b>	None	<b>Motor Standards:</b>	NEMA
<b>Constant Torque Speed Range:</b>	15	<b>Starting Method:</b>	Direct on line
<b>Current @ Voltage:</b>	36.000 A @ 208.0 V	<b>Thermal Device - Bearing:</b>	None
	33.800 A @ 230.0 V	<b>Thermal Device - Winding:</b>	None
	16.900 A @ 460.0 V	<b>Vibration Sensor Indicator:</b>	No Vibration Sensor
<b>Design Code:</b>	A	<b>Winding Thermal 1:</b>	None
<b>Drip Cover:</b>	No Drip Cover	<b>Winding Thermal 2:</b>	None
<b>Duty Rating:</b>	CONT	<b>XP Temp Code:</b>	T3C

<b>Nameplate NP4225L</b>			
<b>CAT.NO.</b>	VXT3152T-210	<b>I.P.</b>	54
<b>SPEC.</b>	07-0000-0932	<b>ENCL</b>	TEFC
<b>FRAME</b>	215TC	<b>H.P.</b>	15
<b>VOLTS</b>	208-230/460	<b>P.F.</b>	91
<b>F.L. AMPS</b>	36-33.8/16.9	<b>RATING</b>	40C AMB-CONT
<b>R.P.M.</b>	3500	<b>USABLE AT 208V</b>	
<b>HZ.</b>	60	<b>PH.</b>	3
<b>SER.F.</b>	1.15	<b>DES.</b>	A
<b>NEMA NOM. EFF.</b>	91	<b>Wk2</b>	0.456
<b>DE</b>	6307	<b>ODE</b>	6206
<b>MAG. CUR.</b>	9.2/4.6	<b>CHP</b>	60
<b>INV TYPE</b>	PWM	<b>TO</b>	90
<b>CT</b>	15	<b>VT</b>	15
<b>TO</b>	60	<b>TO</b>	60
<b>CC</b>	010A	<b>SN</b>	
USABLE AT 50 HZ 12.5 HP			
190/380V 34/17A			

Parts List		
Part Number	Description	Quantity
SA388874	SA 07-0000-0932	1.000 EA
RA379240	RA 07-0000-0932	1.000 EA
LB1115N	LABEL,LIFTING DEVICE (ON ROLLS)	1.000 EA
LC0005E01	CONN.DIA./WARNING LABEL (LC0005/LB1119N)	1.000 EA
07PA1095	PKG GRP, VER 07 CAST IRON	1.000 EA
NP4225L	SS SEVERE DUTY XT INV UL CSA	1.000 EA
85XU0407S04	4X1/4 U DRIVE PIN STAINLESS	2.000 EA
MN416A01	TAG-INSTAL-MAINT no wire (2100/bx) 4/22	1.000 EA
HW3201A05	3/8-16 EYEBOLT	1.000 EA
07FH4007A07	IEC FH NO GRSR, NOTCH @ 6:00 & 3 F/C HOL	1.000 EA
51XW1032A06	10-32 X .38, TAPTITE II, HEX WSHR SLTD S	3.000 EA
36FN3000C02SP	EXFN, PLASTIC, 5.25 OD, 1.175 ID	1.000 EA
51XB1214A16	12-14X1.00 HXWSSLD SERTYB	1.000 EA
MJ1000A02	GREASE, MOBIL POLYREX EM - 124047	0.050 LB
HA3104A32	THRUBOLT- 5/16-18 X12.750	4.000 EA
XY3118A12	5/16-18 HEX NUT DIRECTIONAL SERRATION	4.000 EA
37EP3101C34	FR ENDPLATE, MACH SPL MACH SWITCH BOSSES	1.000 EA
HW4600B36SP	V-RING SLINGER 1.188 X 1.690 X .24 VITON	1.000 EA
HW5100A06	W2420-025 WVY WSHR (WB)	1.000 EA
HA4067A01	PUSH IN DRAIN FITTING (BLACK)	1.000 EA
37EP3300A05	FACE MT EP-ENCL-307 BRG-213TC-215TC LESS	1.000 EA
HW4600B33	V-RING SLINGER 1.375 X 1.890 X .35 VITON	1.000 EA
10XN2520A30	HEX HD CAP SCREW-STD THD-.25 X 20 THD PE	4.000 EA
HW1001A25	LOCKWASHER 1/4, ZINC PLT .493 OD, .255 I	4.000 EA

Parts List (continued)		
Part Number	Description	Quantity
HA4067A01	PUSH IN DRAIN FITTING (BLACK)	1.000 EA
09CB3002SP	CB W/1.38 LEAD HOLE FOR 37, 39, 307 & 30	1.000 EA
09GS1000SP	GASKET-CONDUIT BOX, 1/16 THICK LEXIDE	1.000 EA
51XW2520A12	.25-20 X .75, TAPTITE II, HEX WSHR SLTD	2.000 EA
WD1000B16	T&B CX70TN OR L70P TERMINAL LUG	1.000 EA
59XW2520G07	.25-20X.44,HEX SER WSHR,TAPTITE 2,GREEN	1.000 EA
09CB3501SP	CONDUIT BOX LID FOR 09CB3001 & 09CB3002	1.000 EA
09GS1013SP	GS FOR 09CB3501, 12CB1500 & 12CB1503 LID	1.000 EA
51XW2520A12	.25-20 X .75, TAPTITE II, HEX WSHR SLTD	2.000 EA
MG1025L14	WILKOFAS, 776.14, GRUNDFOS BLACK	0.125 GA
07PA1095	PKG GRP, VER 07 CAST IRON	1.000 EA
07PA1011	PKG GRP, 07 CAST IRON PK1181	1.000 EA
HW2501F21	KEY, 5/16 SQ X 2.375	1.000 EA
HA7000A02	KEY RETAINER RING, 1 1/8 DIA, 1 3/8 DIA	1.000 EA
FE-0000001	ZRTG FE ASSEMBLY	1.000 EA
PE-0000001	ZRTG PE ASSEMBLY	1.000 EA

**AC Induction Motor Performance Data**

Record # 51368


Typical performance - not guaranteed values

<b>Winding: 07WGR536-R001</b>		<b>Type: 0750M</b>		<b>Enclosure: TEFC</b>			
<b>Nameplate Data</b>			<b>460 V, 60 Hz: High Voltage Connection</b>				
<b>Rated Output (HP)</b>	15	<b>Full Load Torque</b>	22.6 LB-FT				
<b>Volts</b>	208-230/460	<b>Start Configuration</b>	direct on line				
<b>Full Load Amps</b>	36-32.2/16.6	<b>Breakdown Torque</b>	87.7 LB-FT				
<b>R.P.M.</b>	3500	<b>Pull-up Torque</b>	29.6 LB-FT				
<b>Hz</b>	60 <b>Phase</b>	3	<b>Locked-rotor Torque</b>	43.2 LB-FT			
<b>NEMA Design Code</b>	A	<b>KVA Code</b>	J	<b>Starting Current</b>	133 A		
<b>Service Factor (S.F.)</b>	1.15		<b>No-load Current</b>	4.61 A			
<b>NEMA Nom. Eff.</b>	91	<b>Power Factor</b>	91	<b>Line-line Res. @ 25°C</b>	0.54448 Ω		
<b>Rating - Duty</b>	40C AMB-CONT		<b>Temp. Rise @ Rated Load</b>	66°C			
<b>S.F. Amps</b>			<b>Temp. Rise @ S.F. Load</b>	84°C			

**Load Characteristics 460 V, 60 Hz, 15 HP**



<b>% of Rated Load</b>	<b>25</b>	<b>50</b>	<b>75</b>	<b>100</b>	<b>125</b>	<b>150</b>	<b>S.F.</b>
<b>Power Factor</b>	65	83	88	91	92	91	92
<b>Efficiency</b>	90.2	92.6	92.5	91.6	90.2	88.6	90.8
<b>Speed</b>	3572	3546.2	3519.8	3490.6	3457.2	3421.4	3471
<b>Line amperes</b>	6.18	9.3	12.9	16.9	21.4	26	19.6

Performance Graph at 460V, 60Hz, 15.0HP Typical performance - Not guaranteed values





07LYL289



07LYL289

CUSTOMER IS RESPONSIBLE FOR DETERMINING THAT BALDOR'S PRODUCT WILL PERFORM SUITABLY IN THE INTENDED APPLICATION.

REV. DESC: "C" LENGTH WAS 19.25	VERSION: 02	TDR: 000001161672
REV. LTR: B	REVISED: 11:07:15 02/24/2021	BY: ENERIO0
FILE: \AAA\00165\767		
MTL: -		

**BALDOR - RELIANCE**®

VERT 213-5TC TEFC W/SEALED BEARINGS

SH 1 of 1

CD0005




LOW VOLTAGE  
(2Y)



LINE

HIGH VOLTAGE  
(1Y)



LINE

NOTES:

1. INTERCHANGE ANY TWO LINE LEADS TO REVERSE ROTATION.
2. OPTIONAL THERMOSTATS ARE PROVIDED WHEN SPECIFIED.
3. ACTUAL NUMBER OF INTERNAL PARALLEL CIRCUITS MAY BE A MULTIPLE OF THOSE SHOWN ABOVE.
4. LEAD COLORS ARE OPTIONAL. LEADS MUST ALWAYS BE NUMBERED AS SHOWN.

REV. DESC: REVISE TO SHOW OPTIONAL COLORS			
REV. LTR: E	BY: JLP	REVISED: 01/19/99 10:15	TDR: 0171435
90000		FILE: AAA00005140	MDL: -
		MTL: -	

**BALDOR ELECTRIC Co.**

3PH, DV, 9 LEADS

CD0005

Marketing maintained PDF of MN416:

<http://www.baldor.com/support/Literature/Load.ashx/MN416?ManNumber=MN416>