BALDOR · RELIANCE II

Product Information Packet

XT31502TS-5

150HP,3570RPM,3PH,60HZ,445TS,TEFC,F1

Specs				
Catalog Number:	XT31502TS-5	Heater Indicator:	No Heater	
Enclosure:	TEFC	Insulation Class:	F	
Frame:	445TS	Inverter Code:	Inverter Ready	
Frame Material:	Iron	IP Rating:	NONE	
Output @ Frequency:	150.000 HP @ 60 HZ	KVA Code:	G	
Synchronous Speed @ Frequency:	3600 RPM @ 60 HZ	Motor Lead Quantity/Wire Size:	3 @ 1 AWG	
Voltage @ Frequency:	575.0 V @ 60 HZ	Motor Type:	A4478M	
XP Class and Group:	None	Mounting Arrangement:	F1	
XP Division:	Division II	Power Factor:	90	
Agency Approvals © All product information	NEMA PREMIUM	Moodyst Family echanical Inc. copyright ©	General Industrial	

	UR	Pulley End Bearing Type:	Ball
Auxillary Box:	No Auxillary Box	Pulley Face Code:	Standard
Base Indicator:	Rigid	Shaft Ground Indicator:	No Shaft Grounding
Bearing Grease Type:	Polyrex EM (-20F +300F)	Shaft Rotation:	Reversible
Current @ Voltage:	131.000 A @ 575.0 V	Shaft Slinger Indicator:	Shaft Slinger
Design Code:	В	Speed Code:	Single Speed
Drip Cover:	No Drip Cover	Motor Standards:	NEMA
Duty Rating:	CONT	Starting Method:	Direct on line
Feedback Device:	NO FEEDBACK	Thermal Device - Bearing:	None
		Thermal Device - Winding:	None

No performance data has been assigned to this product.